

# EQ-KMK630 Part A ADHESIVE

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/15/2015

Revision date: 06/24/2020

Supersedes: 05/15/2015

Version: 1.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Rear View Mirror Adhesive (Part A-Adhesive)  
Product code : EQ-KMK630A

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesive: component

#### 1.3. Supplier

Equalizer Industries, Inc.  
2611 Oakmont Drive  
Round Rock, TX 78665  
800-334-1334

#### 1.4. Emergency telephone number

Emergency number : 1-800-535-50535 INTERNATIONAL: 1-352-323-3500  
INFOTRAC (Available 24 hours/day)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2	H319 Causes serious eye irritation
Specific target organ toxicity (single exposure) Category 3	H335 May cause respiratory irritation
Hazardous to the aquatic environment - Acute Hazard Category 2	H401 Toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation  
H401 - Toxic to aquatic life  
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P261 - Avoid breathing fume, mist, vapors, spray  
P264 - Wash hands, forearms and face thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P280 - Wear eye protection, protective clothing, protective gloves  
P302+P352 - If on skin: Wash with plenty of Wash skin with mild soap and water.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse

# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P270 - Do not eat, drink or smoke when using this product  
P501 - Dispose of contents/container to an approved waste disposal plant

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Urethane Methacrylate Oligomer	(CAS-No.) Proprietary	25 - 60	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
methacrylic acid, stabilized	(CAS-No.) 79-41-4	< 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Aquatic Acute 3, H402
acrylate ester	(CAS-No.) 5888-33-5	< 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
maleic acid	(CAS-No.) 110-16-7	< 5	Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice.  
First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
First-aid measures after skin contact : Wash with plenty of soap and water.  
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
First-aid measures after ingestion : Do NOT induce vomiting. Immediately consult a doctor/medical service.

### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : If you feel unwell, seek medical advice.  
Symptoms/effects after inhalation : Irritation of the respiratory tract.  
Symptoms/effects after skin contact : Causes skin irritation.  
Symptoms/effects after eye contact : Causes serious eye irritation.  
Symptoms/effects after ingestion : Gastrointestinal complaints.  
Chronic symptoms : May cause an allergic skin reaction. May cause dermatitis by skin contact.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : carbon dioxide (CO<sub>2</sub>), dry chemical powder, foam.

### 5.2. Specific hazards arising from the chemical

No additional information available

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire.  
Protection during firefighting : Firefighters should wear positive pressure self contained breathing apparatus (SCBA) and full turnout gear.

# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Hazardous combustion products: . carbon oxides (CO and CO<sub>2</sub>). Nitrogen oxides. Other toxic vapors.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

##### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Protective clothing. Safety glasses.

Emergency procedures : Ensure adequate ventilation, especially in confined areas. Evacuate unnecessary personnel. In case of hazardous reactions: keep upwind.

##### 6.1.2. For emergency responders

Protective equipment : In case of insufficient ventilation, wear suitable respiratory equipment. Wear recommended personal protective equipment. Use chemically protective clothing. Chemical goggles or face shield with safety glasses. Avoid breathing vapors.

Emergency procedures : Ventilate area. Stop release. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill.

Methods for cleaning up : Take up liquid spill into inert absorbent material. Absorbed substance: shovel into drums.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing vapors. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Observe normal hygiene standards. Use personal protective equipment as required.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use.

Storage temperature : ≤ 38 °C

Storage area : Keep container in a well-ventilated place. Keep container tightly closed. Meet the legal requirements. Store in a dry area. Store in a well-ventilated place.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

<b>Urethane Methacrylate Oligomer (Proprietary)</b>		
Not applicable		
<b>methacrylic acid, stabilized (79-41-4)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
<b>maleic acid (110-16-7)</b>		
Not applicable		
<b>acrylate ester (5888-33-5)</b>		
Not applicable		

#### 8.2. Appropriate engineering controls

No additional information available

# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless liquid. : Colourless : There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Characteristic odour Repulsive odour Irritating/pungent odour Pleasant odour Almost odourless Odourless Vinegar odour Mild odour Ester smell Camphor odour Unpleasant odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Poorly soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. irritating organic vapors. Oxides of Nitrogen.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>methacrylic acid, stabilized (79-41-4)</b>	
LD50 oral rat	1320 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rabbit	500 - 1000 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	7.1 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value, Inhalation (mixture of vapour and aerosol))
ATE US (oral)	1320 mg/kg body weight
ATE US (dermal)	500 mg/kg body weight

<b>maleic acid (110-16-7)</b>	
LD50 oral rat	2870 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	2620 mg/kg (Equivalent or similar to OECD 402, Rabbit, Female, Read-across, Dermal)
ATE US (oral)	2870 mg/kg body weight
ATE US (dermal)	2620 mg/kg body weight

<b>acrylate ester (5888-33-5)</b>	
LD50 oral rat	4890 mg/kg (Rat, Literature, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature, Dermal)
ATE US (oral)	4890 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
  
Reproductive toxicity : Not classified  
Specific target organ toxicity – single exposure : May cause respiratory irritation.

<b>Urethane Methacrylate Oligomer (Proprietary)</b>	
Specific target organ toxicity – single exposure	May cause respiratory irritation.

<b>acrylate ester (5888-33-5)</b>	
Specific target organ toxicity – single exposure	May cause respiratory irritation.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified  
Viscosity, kinematic : No data available  
  
Symptoms/effects : If you feel unwell, seek medical advice.  
Symptoms/effects after inhalation : Irritation of the respiratory tract.  
Symptoms/effects after skin contact : Causes skin irritation.  
Symptoms/effects after eye contact : Causes serious eye irritation.  
Symptoms/effects after ingestion : Gastrointestinal complaints.  
Chronic symptoms : May cause an allergic skin reaction. May cause dermatitis by skin contact.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>methacrylic acid, stabilized (79-41-4)</b>	
LC50 fish 1	85 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	> 130 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, GLP)

# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>methacrylic acid, stabilized (79-41-4)</b>	
ErC50 (algae)	45 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
<b>maleic acid (110-16-7)</b>	
LC50 fish 1	106 mg/l (DIN 38412-15, 48 h, Leuciscus idus, Fresh water, Weight of evidence)
EC50 Daphnia 1	42.81 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	74.35 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
<b>acrylate ester (5888-33-5)</b>	
LC50 fish 1	0.704 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	1.98 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

### 12.2. Persistence and degradability

<b>methacrylic acid, stabilized (79-41-4)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.89 g O <sub>2</sub> /g substance
ThOD	1.67 g O <sub>2</sub> /g substance
<b>maleic acid (110-16-7)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.38 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.83 g O <sub>2</sub> /g substance
ThOD	0.83 g O <sub>2</sub> /g substance
<b>acrylate ester (5888-33-5)</b>	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>methacrylic acid, stabilized (79-41-4)</b>	
BCF other aquatic organisms 1	3 (Calculated value)
Log Pow	0.93 (Experimental value, 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>maleic acid (110-16-7)</b>	
Log Pow	-1.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Not bioaccumulative.
<b>acrylate ester (5888-33-5)</b>	
BCF fish 1	37 (OECD 305: Bioconcentration: Flow-Through Fish Test, 56 h, Danio rerio, Flow-through system, Fresh water, Read-across, GLP)
Log Pow	4.52 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).

### 12.4. Mobility in soil

<b>methacrylic acid, stabilized (79-41-4)</b>	
Surface tension	0.0659 N/m (20 °C, 1.01 g/l, EU Method A.5: Surface tension)
Ecology - soil	Highly mobile in soil.
<b>maleic acid (110-16-7)</b>	
Ecology - soil	No (test)data on mobility of the substance available.
<b>acrylate ester (5888-33-5)</b>	
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

No additional information available

# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

No additional information available

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Other information : No supplementary information available.

#### TDG

#### Transport by sea

Transport document description (IMDG) : UN 1760 CORROSIVE LIQUID, N.O.S. (contains Methacrylic Acid and Maleic Acid), 8, II  
UN-No. (IMDG) : 1760  
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S.  
Class (IMDG) : 8 - Corrosive substances  
Packing group (IMDG) : II - substances presenting medium danger  
Limited quantities (IMDG) : 0

#### Air transport

Transport document description (IATA) : UN 1760 Corrosive liquid, n.o.s. (contains Methacrylic Acid and Maleic Acid), 8, II  
UN-No. (IATA) : 1760  
Proper Shipping Name (IATA) : Corrosive liquid, n.o.s.  
Class (IATA) : 8 - Corrosives  
Packing group (IATA) : II - Medium Danger

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

<b>KMK630A</b>	
EPA TSCA Regulatory Flag	All components of this product are listed on the TSCA Inventory of Chemical Substances or are exempt from listing.
<b>methacrylic acid, stabilized (79-41-4)</b>	
EPA TSCA Regulatory Flag	All components of this product are listed on the TSCA Inventory of Chemical Substances or are exempt from listing.
CERCLA RQ	None
SARA Section 302 Threshold Planning Quantity (TPQ)	None
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
<b>maleic acid (110-16-7)</b>	
EPA TSCA Regulatory Flag	All components of this product are listed on the TSCA Inventory of Chemical Substances or are exempt from listing.
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard
<b>acrylate ester (5888-33-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

#### 15.2. International regulations

#### CANADA

No additional information available

# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### acrylate ester (5888-33-5)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

#### KMK630A

Components of this product are listed or exempt from listing on the Canadian Domestic Substance List.

#### methacrylic acid, stabilized (79-41-4)

All components of this product are listed or exempted from listing under:  
TSCA(US), DSL(CDN), AICS(AUS), METI (JPN), ECL(KOR), PICCS(RP), IECSC(CN), HSNO(NZ)

#### maleic acid (110-16-7)

Components of this product are listed or exempt from listing on the Canadian Domestic Substance List.

### 15.3. US State regulations

**⚠ WARNING:** This product can expose you to ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/24/2020


Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



# EQ-KMK630A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

Hazard Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

*This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the Supplier's knowledge, or is obtained from sources believed by the Supplier to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Supplier assumes no responsibility for injuries proximately caused by the use of the Material if reasonable safety procedures are followed as stipulated in the Data Sheet. Additionally, the Supplier assumes no responsibility for injuries caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in the use of the Materials.*